


KVMP 45/29-Z28

Cable gland circular, brass, DIN 89280, M45-Pg29



Products may differ in size, colour and appearance to those shown. If you require further information or customisation, please contact us directly.



Material cable gland	Brass
Material sealing gasket	EPDM
Material earthing insert	Brass chromium-plated
Temp. range min	-40 °C
Temp. range max	100 °C
Protection class	IP54
Thread type	PG
Ø Connection thread D	29
Length screw-in thread L	11 mm
Ø cable diameter min	26 mm
Ø cable diameter max	28,5 mm
Key width SW	46 mm
Collar diameter (E)	50 mm
Total length TL	59 mm
Install. torques fitting	20 N m
Install. torques cap nut	15 N m
Surface	Bright
Order no. bright	10010998
Type	KVMP 45/29-Z28
Packing unit	1
Tariff number	85369010
EAN number	4007685109987

20.09.2026

Your Contact:

WISKA Hoppmann GmbH

Kisdorfer Weg 28 · 24568 Kaltenkirchen · Germany

☎ +49-4191-508-0 · 📠 +49-4191-508-209

contact@wiska.de · www.wiska.com



Your Contact:

WISKA Hoppmann GmbH

Kisdorfer Weg 28 · 24568 Kaltenkirchen · Germany

☎ +49-4191-508-0 · 📠 +49-4191-508-209

contact@wiska.de · www.wiska.com