

KVM 105-Z75/Ni

Cable gland, brass nickel-plated, DIN 89280, M105



Products may differ in size, colour and appearance to those shown. If you require further information or customisation, please contact us directly.



Material cable gland	Brass nickel-plated
Material sealing gasket	EPDM
Material earthing insert	Brass chromium-plated
Temp. range min	-40 °C
Temp. range max	100 °C
Protection class	IP54
Thread type	M
Ø Connection thread D	105
Lead	2
Length screw-in thread L	20 mm
Ø cable diameter min	73 mm
Ø cable diameter max	78 mm
Key width SW	105 mm
Collar diameter (E)	113 mm
Total length TL	88 mm
Install. torques fitting	30 N m
Install. torques cap nut	30 N m
Impact category	6
Advice	* Similar to DIN 89280
Surface	Nickel-plated
Order no. nickel-plated	10014554
Type	KVM 105-Z75/Ni
Packing unit	1
Tariff number	85369010
EAN number	4007685145541

Your Contact:

WISKA Hoppmann GmbH

Kisdorfer Weg 28 · 24568 Kaltenkirchen · Germany

☎ +49-4191-508-0 · 📠 +49-4191-508-209

contact@wiska.de · www.wiska.com

ETIM-Classification

EC000441

Recommended accessories

GM 105/Ni

10011708

23.05.2026

Your Contact:

WISKA Hoppmann GmbH

Kisdorfer Weg 28 · 24568 Kaltenkirchen · Germany

 +49-4191-508-0 ·  +49-4191-508-209

contact@wiska.de · www.wiska.com



Your Contact:
WISKA Hoppmann GmbH
Kisdorfer Weg 28 · 24568 Kaltenkirchen · Germany
☎ +49-4191-508-0 · 📠 +49-4191-508-209
contact@wiska.de · www.wiska.com