


## EVS 40 LG

Stop end, polystyrene, RAL 7035, M40



Products may differ in size, colour and appearance to those shown. If you require further information or customisation, please contact us directly.

<b>Material</b>	Polystyrene, impact resistant
<b>Temp. range min</b>	-20 °C
<b>Temp. range max</b>	60 °C
<b>Protection class</b>	IP56
<b>Advice</b>	with sealing IP66/IP68
<b>Thread type</b>	M
<b>Ø Connection thread D</b>	40
<b>Lead</b>	1,5
<b>Length screw-in thread L</b>	8 mm
<b>Total length TL</b>	13 mm
<b>External diameter ED</b>	46 mm
<b>Product Color</b>	RAL 7035
<b>Order no. RAL 7035</b>	10062495
<b>Type</b>	EVS 40 LG
<b>Packing unit</b>	50
<b>EAN number</b>	4007685624954
<b>Tariff number</b>	39269097
<b>ETIM-Classification</b>	EC000032

### Recommended accessories

<b>EMUG 40 LG</b>	10060775
<b>EADR 40</b>	10062806

23.05.2026

Your Contact:

**WISKA Hoppmann GmbH**

Kisdorfer Weg 28 · 24568 Kaltenkirchen · Germany

☎ +49-4191-508-0 · 📠 +49-4191-508-209

contact@wiska.de · www.wiska.com



Your Contact:

**WISKA Hoppmann GmbH**

Kisdorfer Weg 28 · 24568 Kaltenkirchen · Germany

☎ +49-4191-508-0 · 📠 +49-4191-508-209

contact@wiska.de · www.wiska.com