


EX-EVSG 25

EX stop end, polyamide, M25



Products may differ in size, colour and appearance to those shown. If you require further information or customisation, please contact us directly.



Material	Polyamide
Material sealing gasket	EPDM
Temp. range min	-40 °C
Temp. range max	75 °C
Protection class	IP66 / IP68 (5 bar 30 min)
Type of protection	Ex eb, Ex tb
Ex-Certificate	ATEX, IECEx
Product Color	RAL 9005
Thread type	M
Ø Connection thread D	25
Lead	1,5
Length screw-in thread L	15 mm
Key width SW1	29 mm
Key width SW2	8 mm
Collar diameter E1	31 mm
Collar diameter E2	9 mm
Total length TL	20 mm
Order no. RAL 9005	10065303
Type	EX-EVSG 25
Packing unit	100
EAN number	4007685653039
Tariff number	39269097
ETIM-Classification	EC000032

Your Contact:

WISKA Hoppmann GmbH

Kisdorfer Weg 28 · 24568 Kaltenkirchen · Germany

☎ +49-4191-508-0 · 📠 +49-4191-508-209

contact@wiska.de · www.wiska.com

Recommended accessories

EMUG 25 BK

10061783

11.08.2026

Your Contact:


WISKA Hoppmann GmbH

Kisdorfer Weg 28 · 24568 Kaltenkirchen · Germany

 +49-4191-508-0 ·  +49-4191-508-209

contact@wiska.de · www.wiska.com

Other technical data on request / subject to change without notice



Your Contact:

WISKA Hoppmann GmbH

Kisdorfer Weg 28 · 24568 Kaltenkirchen · Germany

☎ +49-4191-508-0 · 📠 +49-4191-508-209

contact@wiska.de · www.wiska.com