

MFD 25/01/090

Multiple sealing insert



Products may differ in size, colour and appearance to those shown. If you require further information or customisation, please contact us directly.



| | |
|------------------------------|-------------------------|
| Material | Thermoplastic elastomer |
| Temp. range min | -40 °C |
| Temp. range max | 100 °C |
| Protection class | IP66 / IP68 |
| Ø cable diameter min | 7 mm |
| Ø cable diameter max | 9 mm |
| Quantity of cable | 1 |
| BxL | 20,6 x 11,5 mm |
| Product Color | RAL 9005 |
| Using for cable gland | SPRINT 25 |
| Order no. RAL 9005 | 10101016 |
| Type | MFD 25/01/090 |
| Packing unit | 25 |
| EAN number | 4007685040839 |
| Tariff number | 39269097 |
| ETIM-Classification | EC000441 |

Remarks:

IP68: Ø cable diameter min. = Ø cable diameter max. - 10%, but not bigger than 1 mm under the Ø cable diameter max.

IP66: 1 cable Ø 7 - 9 mm

12.05.2026

Your Contact:

WISKA Hoppmann GmbH

Kisdorfer Weg 28 · 24568 Kaltenkirchen · Germany

☎ +49-4191-508-0 · 📠 +49-4191-508-209

contact@wiska.de · www.wiska.com