

## Ex-5516/ST/4h/1x24-Z14

Ex plug 16A 130V, brass, IP66



Products may differ in size, colour and appearance to those shown. If you require further information or customisation, please contact us directly.



<b>WISKA-Order no.</b>	10101756
<b>Type</b>	Ex-5516/ST/4h/1x24-Z14
<b>Material</b>	Brass
<b>Voltage</b>	130 V
<b>Voltage max. (V)</b>	400 V
<b>Type of Voltage</b>	AC
<b>Current</b>	16 A
<b>Protection class</b>	IP56
<b>plug insert</b>	EXPORT
<b>Clock face position</b>	4h
<b>Temp. range min</b>	-40 °C
<b>Temp. range max</b>	40 °C
<b>Type of cable gland</b>	M 24 x 1,5
<b>Ø cable diameter min</b>	12 mm
<b>Ø cable diameter max</b>	14,5 mm
<b>Type of cable</b>	armoured
<b>Marking</b>	II 2 D Ex tb IIIC T65°C Db, II 2 G Ex de IIC T6...T5 Gb
<b>Approval</b>	TÜV 14 ATEX 7565X, IECEx TUR 15.0018X
<b>Explosion Groups</b>	IIC, IIIC
<b>Temp.-class</b>	T6
<b>Zone</b>	1, 21
<b>Approval</b>	DNV-GL, RMRS
<b>Weight</b>	1,31 kg

Remarks:

Your Contact:

**WISKA Hoppmann GmbH**

Kisdorfer Weg 28 · 24568 Kaltenkirchen · Germany

☎ +49-4191-508-0 · 📠 +49-4191-508-209

contact@wiska.de · www.wiska.com

- 4h - 2-pole + E, 110V-130V
- Flameproof enclosed interior
- Temperature range -40°C - +55°C = T5

## Spare parts

SP-55161-ATEX Ex plug interior

22000415

12.05.2026

Your Contact:

**WISKA Hoppmann GmbH**

Kisdorfer Weg 28 · 24568 Kaltenkirchen · Germany

 +49-4191-508-0 ·  +49-4191-508-209

contact@wiska.de · www.wiska.com