

## MFD 12/01/015

### Multiple sealing insert



Products may differ in size, colour and appearance to those shown. If you require further information or customisation, please contact us directly.



<b>Material</b>	Thermoplastic elastomer
<b>Temp. range min</b>	-40 °C
<b>Temp. range max</b>	100 °C
<b>Protection class</b>	IP66 / IP68
<b>Ø cable diameter min</b>	0,5 mm
<b>Ø cable diameter max</b>	1,5 mm
<b>Quantity of cable</b>	1
<b>BxL</b>	9,6 x 6,7 mm
<b>Product Color</b>	RAL 9005
<b>Using for cable gland</b>	SPRINT 12
<b>Order no. RAL 9005</b>	10102489
<b>Type</b>	MFD 12/01/015
<b>Packing unit</b>	25
<b>EAN number</b>	4007685060257
<b>Tariff number</b>	40161000
<b>ETIM-Classification</b>	EC000441

#### Remarks:

IP68: Ø cable diameter min. = Ø cable diameter max. - 10%, but not bigger than 1 mm under the Ø cable diameter max.

IP66: 1 cable Ø 0,5 - 1,5 mm

12.05.2026

#### Your Contact:

**WISKA Hoppmann GmbH**  
 Kisdorfer Weg 28 · 24568 Kaltenkirchen · Germany  
 ☎ +49-4191-508-0 · 📠 +49-4191-508-209  
 contact@wiska.de · www.wiska.com