

## MFD 25/02/070-01/040 RW

Railway multiple sealing insert, TPE, white, M25



Products may differ in size, colour and appearance to those shown. If you require further information or customisation, please contact us directly.



<b>Material</b>	Thermoplastic elastomer
<b>Hazard level EN acc. 45545</b>	R22=HL3 / R23=HL3 / R24=HL3
<b>Temp. range min</b>	-40 °C
<b>Temp. range max</b>	100 °C
<b>Protection class</b>	IP66 / IP68
<b>Ø cable diameter min</b>	3 mm
<b>Ø cable diameter max</b>	7 mm
<b>Quantity of cable</b>	3
<b>BxL</b>	20,6 x 11,5 mm
<b>Using for cable gland</b>	SPRINT 25
<b>Product Color</b>	RAL 9010
<b>WISKA-Order no.</b>	10105550
<b>Type</b>	MFD 25/02/070-01/040 RW
<b>Packing unit</b>	25
<b>EAN number</b>	4007686010411
<b>Tariff number</b>	40161000
<b>ETIM-Classification</b>	EC000441

Remarks:

- IP68: Ø cable diameter min. = Ø cable diameter max. - 10%, but not bigger than 1 mm under the Ø cable diameter max.

- IP66: for cable entries

2 x 5,0 - 7,0 mm Ø

1 x 2,0 - 4,0 mm Ø

23.05.2026

Your Contact:

**WISKA Hoppmann GmbH**

Kisdorfer Weg 28 · 24568 Kaltenkirchen · Germany

☎ +49-4191-508-0 · 📠 +49-4191-508-209

contact@wiska.de · www.wiska.com