

## MFD 16/05/020

Multiple sealing insert



Products may differ in size, colour and appearance to those shown. If you require further information or customisation, please contact us directly.



<b>Material</b>	Thermoplastic elastomer
<b>Temp. range min</b>	-40 °C
<b>Temp. range max</b>	100 °C
<b>Protection class</b>	IP66 / IP68
<b>Ø cable diameter min</b>	1 mm
<b>Ø cable diameter max</b>	2 mm
<b>Quantity of cable</b>	5
<b>BxL</b>	13 x 9,7 mm
<b>Product Color</b>	RAL 9005
<b>Using for cable gland</b>	SPRINT 16
<b>Order no. RAL 9005</b>	10105950
<b>Type</b>	MFD 16/05/020
<b>Packing unit</b>	25
<b>EAN number</b>	4007686014150
<b>Tariff number</b>	39269097

Remarks:

IP68: Ø cable diameter min. = Ø cable diameter max. - 10%, but not bigger than 1 mm under the Ø cable diameter max.

IP66: 5 cables Ø 1 - 2 mm

12.05.2026

Your Contact:

**WISKA Hoppmann GmbH**

Kisdorfer Weg 28 · 24568 Kaltenkirchen · Germany

☎ +49-4191-508-0 · 📠 +49-4191-508-209

contact@wiska.de · www.wiska.com