

BCA-S-14-BG

Conduit PA6 UL94-V0, RAL 7031, NW14



Products may differ in size, colour and appearance to those shown. If you require further information or customisation, please contact us directly.



Material	PA6 UL94-V0
Temp. range min	-40 °C
Temp. range max	140 °C
Operational areas	EN 45545 - Railway
Product Color	RAL 7031
NW	14
External diameter ED	18,5 mm
Ø inside	14,2 mm
Profile width A	3,3 mm
Width B	2,3 mm
Bending radius R	50 mm
Wall thickness S	0,3 mm
Model	Standard profile
UL 1696	No
Type	BCA-S-14-BG
Order no. RAL 7031	10107081
Packing unit	50 m
EAN number	4007686036930
Tariff number	39173900
ETIM-Classification	EC001177

Recommended accessories

EBFS-14-20-BG	10106849
----------------------	----------

Your Contact:

WISKA Hoppmann GmbH

Kisdorfer Weg 28 · 24568 Kaltenkirchen · Germany

☎ +49-4191-508-0 · 📠 +49-4191-508-209

contact@wiska.de · www.wiska.com

EMBFS-14-20-BG

10106882

BCC-14-BG

10106933

12.05.2026

Your Contact:

WISKA Hoppmann GmbH

Kisdorfer Weg 28 · 24568 Kaltenkirchen · Germany

☎ +49-4191-508-0 · 📠 +49-4191-508-209

contact@wiska.de · www.wiska.com



Your Contact:

WISKA Hoppmann GmbH

Kisdorfer Weg 28 · 24568 Kaltenkirchen · Germany

☎ +49-4191-508-0 · 📠 +49-4191-508-209

contact@wiska.de · www.wiska.com



Your Contact:

WISKA Hoppmann GmbH

Kisdorfer Weg 28 · 24568 Kaltenkirchen · Germany

☎ +49-4191-508-0 · 📠 +49-4191-508-209

contact@wiska.de · www.wiska.com