

BCAV-S-14-BK

Conduit PA6 UL94-V2, RAL 9005, NW14



Products may differ in size, colour and appearance to those shown. If you require further information or customisation, please contact us directly.



Material	PA6 UL94-V2
Temp. range min	-40 °C
Temp. range max	125 °C
Operational areas	Mechanical plant engineering
Product Color	RAL 9005
NW	14
External diameter ED	18,5 mm
Ø inside	14,2 mm
Profile width A	3,3 mm
Width B	2,3 mm
Bending radius R	50 mm
Wall thickness S	0,3 mm
Model	Standard profile
Type	BCAV-S-14-BK
Order no. RAL 9005	10107089
Packing unit	50 m
EAN number	4007686037098
Tariff number	39173900
ETIM-Classification	EC001175

Recommended accessories

EBFS-14-20-BK	10106866
EMBFS-14-20-BK	10106898

Your Contact:

WISKA Hoppmann GmbH
Kisdorfer Weg 28 · 24568 Kaltenkirchen · Germany
☎ +49-4191-508-0 · 📠 +49-4191-508-209
contact@wiska.de · www.wiska.com

23.05.2026

Your Contact:
WISKA Hoppmann GmbH
Kisdorfer Weg 28 · 24568 Kaltenkirchen · Germany
 +49-4191-508-0 ·  +49-4191-508-209
contact@wiska.de · www.wiska.com



Your Contact:

WISKA Hoppmann GmbH

Kisdorfer Weg 28 · 24568 Kaltenkirchen · Germany

☎ +49-4191-508-0 · 📠 +49-4191-508-209

contact@wiska.de · www.wiska.com



Your Contact:
WISKA Hoppmann GmbH
Kisdorfer Weg 28 · 24568 Kaltenkirchen · Germany
☎ +49-4191-508-0 · 📠 +49-4191-508-209
contact@wiska.de · www.wiska.com