


## EMBF90CG-29-32-BK

Conduit fitting with cable gland, 90° angle, plastic/brass, RAL 9005, NW29



Products may differ in size, colour and appearance to those shown. If you require further information or customisation, please contact us directly.



<b>Material Conduit fitting</b>	polyamide UL94-V0
<b>Material Connection thread</b>	Brass nickel-plated
<b>Material sealing gasket</b>	TPU
<b>Protection class</b>	IP68, IP66
<b>Temp. range min</b>	-40 °C
<b>Temp. range max</b>	100 °C
<b>Operational areas</b>	EN 45545 - Railway
<b>NW</b>	29
<b>Thread type</b>	M
<b>Ø Connection thread D</b>	32
<b>Lead</b>	1,5
<b>Length screw-in thread L</b>	8 mm
<b>Ø closure VD</b>	44,4 mm
<b>Ø inside</b>	21 mm
<b>Key width SW1</b>	41 mm
<b>Key width SW2</b>	36 mm
<b>Width B</b>	109 mm
<b>Total length TL</b>	106,3 mm - 114,3 mm
<b>Type of conduit fitting</b>	90° Angle
<b>Product Color</b>	RAL 9005
<b>Type</b>	EMBF90CG-29-32-BK
<b>Order no. RAL 9005</b>	10108010
<b>Packing unit</b>	25
<b>EAN number</b>	4007686055207
<b>Tariff number</b>	74122000

Your Contact:

WISKA Hoppmann GmbH

Kisdorfer Weg 28 · 24568 Kaltenkirchen · Germany

☎ +49-4191-508-0 · 📠 +49-4191-508-209

contact@wiska.de · www.wiska.com

ETIM-Classification

EC001176

## Recommended accessories

<b>EMMU 32</b>	10063145
<b>BCA-S-29-BK</b>	10107077
<b>BCAV-S-29-BK</b>	10107092
<b>BCIV-S-29-BK</b>	10107109
<b>BCA-29-D-BK</b>	10107124
<b>BCAV-29-D-BK</b>	10107138
<b>BCAB-L-29-BK</b>	10109187
<b>BCAV-H-29-BK</b>	10109204
<b>BCIB-H-29-BK</b>	10109226

26.06.2026


Your Contact:

**WISKA Hoppmann GmbH**

Kisdorfer Weg 28 · 24568 Kaltenkirchen · Germany

☎ +49-4191-508-0 · 📠 +49-4191-508-209

contact@wiska.de · www.wiska.com



Your Contact:

**WISKA Hoppmann GmbH**

Kisdorfer Weg 28 · 24568 Kaltenkirchen · Germany

☎ +49-4191-508-0 · 📠 +49-4191-508-209

contact@wiska.de · www.wiska.com