


BMCG-PVC-S-27-LG

Conduit, galvanized steel, PVC coated, smooth, RAL 7035, NW27



Products may differ in size, colour and appearance to those shown. If you require further information or customisation, please contact us directly.



Material	galvanized steel
Sheathing material 1st coating	PVC
Surface	smooth
Product Color	RAL 7005
Protection class	IP67
Temp. range min	-15 °C
Temp. range max	80 °C
Operational areas	Mechanical plant engineering
NW	27
External diameter ED	33 mm
Ø inside	26,5 mm
Bending radius R	120 mm
Type	BMCG-PVC-S-27-LG
WISKA-Order no.	10109035
Packing unit	30 m
EAN number	4007686079647
Tariff number	83071000
ETIM-Classification	EC001179

Recommended accessories

EMBMFS-S-27-25	10109105
EMBMFS-S-27-32	10109107

28.07.2026


Your Contact:

WISKA Hoppmann GmbH

Kisdorfer Weg 28 · 24568 Kaltenkirchen · Germany

☎ +49-4191-508-0 · 📠 +49-4191-508-209

contact@wiska.de · www.wiska.com



Your Contact:

WISKA Hoppmann GmbH

Kisdorfer Weg 28 · 24568 Kaltenkirchen · Germany

☎ +49-4191-508-0 · 📠 +49-4191-508-209

contact@wiska.de · www.wiska.com

Other technical data on request / subject to change without notice