


BMCG-PVC-S-21-LG-GT

Conduit galvanized steel PVC coated greater temperature range RAL 7035 NW21



Products may differ in size, colour and appearance to those shown. If you require further information or customisation, please contact us directly.



Material	galvanized steel
Sheathing material 1st coating	PVC
Surface	smooth
Product Color	RAL 7005
Protection class	IP67
Temp. range min	-40 °C
Temp. range max	105 °C
Operational areas	Hygienic design, Mechanical plant engineering
NW	21
External diameter ED	27 mm
Ø inside	20,5 mm
Bending radius R	90 mm
Type	BMCG-PVC-S-21-LG-GT
WISKA-Order no.	10109050
Packing unit	30 m
EAN number	4007686079913
Tariff number	83071000
ETIM-Classification	EC001179

Recommended accessories

EMBMFS-S-21-20	10109101
EMBMFS-S-21-25	10109103

23.05.2026


Your Contact:

WISKA Hoppmann GmbH

Kisdorfer Weg 28 · 24568 Kaltenkirchen · Germany

☎ +49-4191-508-0 · 📠 +49-4191-508-209

contact@wiska.de · www.wiska.com



Your Contact:

WISKA Hoppmann GmbH

Kisdorfer Weg 28 · 24568 Kaltenkirchen · Germany

☎ +49-4191-508-0 · 📠 +49-4191-508-209

contact@wiska.de · www.wiska.com