


BMCG-PVC-S-50-LG-GT

Conduit galvanized steel PVC coated greater temperature range RAL 7035 NW50



Products may differ in size, colour and appearance to those shown. If you require further information or customisation, please contact us directly.



Material	galvanized steel
Sheathing material 1st coating	PVC
Surface	smooth
Product Color	RAL 7005
Protection class	IP67
Temp. range min	-40 °C
Temp. range max	105 °C
Operational areas	Mechanical plant engineering, Hygienic design
NW	50
External diameter ED	56 mm
Ø inside	50,5 mm
Bending radius R	200 mm
Type	BMCG-PVC-S-50-LG-GT
Packing unit	25 m
EAN number	4007686079999
Tariff number	83071000
ETIM-Classification	EC001179

Recommended accessories

EMBMFS-S-50-50	10109117
EMBMFS-S-50-63	10109119

28.07.2026


Your Contact:

WISKA Hoppmann GmbH

Kisdorfer Weg 28 · 24568 Kaltenkirchen · Germany

☎ +49-4191-508-0 · 📠 +49-4191-508-209

contact@wiska.de · www.wiska.com



Your Contact:

WISKA Hoppmann GmbH

Kisdorfer Weg 28 · 24568 Kaltenkirchen · Germany

☎ +49-4191-508-0 · 📠 +49-4191-508-209

contact@wiska.de · www.wiska.com

Other technical data on request / subject to change without notice