


BMCG-PU-C-16-LG

Conduit, galvanized steel, PU coated, corrugated, RAL 7035, NW16



Products may differ in size, colour and appearance to those shown. If you require further information or customisation, please contact us directly.



BRACE



Material	galvanized steel
Sheathing material 1st coating	PU
Surface	corrugated
Product Color	RAL 7005
Protection class	IP67
Temp. range min	-55 °C
Temp. range max	120 °C
Operational areas	EN 45545 - Railway
NW	16
External diameter ED	19,5 mm
Ø inside	15,5 mm
Bending radius R	55 mm
Type	BMCG-PU-C-16-LG
WISKA-Order no.	10109073
Packing unit	30 m
EAN number	4007686080353
Tariff number	83071000
ETIM-Classification	EC001179

Recommended accessories

EMBMFS-C-16-16	10109096
EMBMFS-C-16-20	10109098
EMBMFS-C-16-25	10109100

Your Contact:

WISKA Hoppmann GmbH


Kisdorfer Weg 28 · 24568 Kaltenkirchen · Germany

☎ +49-4191-508-0 · 📠 +49-4191-508-209

contact@wiska.de · www.wiska.com

23.05.2026

Your Contact:
WISKA Hoppmann GmbH
Kisdorfer Weg 28 · 24568 Kaltenkirchen · Germany
 +49-4191-508-0 ·  +49-4191-508-209
contact@wiska.de · www.wiska.com



Your Contact:

WISKA Hoppmann GmbH

Kisdorfer Weg 28 · 24568 Kaltenkirchen · Germany

☎ +49-4191-508-0 · 📠 +49-4191-508-209

contact@wiska.de · www.wiska.com