

MFD 40/06/090 RW

Railway multiple sealing insert, TPE, white, M40



Products may differ in size, colour and appearance to those shown. If you require further information or customisation, please contact us directly.



| | |
|-----------------------------------|-----------------------------|
| Material | Thermoplastic elastomer |
| Hazard level EN acc. 45545 | R22=HL3 / R23=HL3 / R24=HL3 |
| Temp. range min | -40 °C |
| Temp. range max | 100 °C |
| Protection class | IP66 / IP68 |
| Ø cable diameter min | 7 mm |
| Ø cable diameter max | 9 mm |
| Quantity of cable | 6 |
| BxL | 35,6 x 18,3 mm |
| Using for cable gland | SPRINT 40 |
| Product Color | RAL 9010 |
| WISKA-Order no. | 10110477 |
| Type | MFD 40/06/090 RW |
| Packing unit | 25 |
| EAN number | 4007686203219 |
| Tariff number | 39269097 |
| ETIM-Classification | EC000441 |

Remarks:

- IP68: Ø cable diameter min. = Ø cable diameter max. - 10%, but not bigger than 1 mm under the Ø cable diameter max.

12.05.2026

Your Contact:

WISKA Hoppmann GmbH

Kisdorfer Weg 28 · 24568 Kaltenkirchen · Germany

☎ +49-4191-508-0 · 📠 +49-4191-508-209

contact@wiska.de · www.wiska.com