

MFD 25/01/094-01/058 RW

Railway multiple sealing insert, TPE, white, M25



Products may differ in size, colour and appearance to those shown. If you require further information or customisation, please contact us directly.



Material	Thermoplastic elastomer
Hazard level EN acc. 45545	R22=HL3 / R23=HL3 / R24=HL3
Temp. range min	-40 °C
Temp. range max	100 °C
Protection class	IP66 / IP68
Ø cable diameter min	3,8 mm
Ø cable diameter max	9,4 mm
Quantity of cable	2
BxL	20,6 x 11,5 mm
Using for cable gland	SPRINT 25
Product Color	RAL 9010
WISKA-Order no.	10110521
Type	MFD 25/01/094-01/058 RW
Packing unit	25
EAN number	4007686211320
Tariff number	39269097
ETIM-Classification	EC000441

Remarks:

- IP68: Ø cable diameter min. = Ø cable diameter max. - 10%, but not bigger than 1 mm under the Ø cable diameter max.
- IP66: for cable entries
 - 1 x 7,4 - 9,4 mm Ø
 - 1 x 3,8 - 5,8 mm Ø

12.05.2026

Your Contact:

WISKA Hoppmann GmbH
 Kisdorfer Weg 28 · 24568 Kaltenkirchen · Germany
 ☎ +49-4191-508-0 · 📠 +49-4191-508-209
 contact@wiska.de · www.wiska.com