

D210/1204/IP/PTZ/P/0M

IP Dome camera, electrical Pan/Tilt, Preset, Zoom 4x optical



Products may differ in size, colour and appearance to those shown. If you require further information or customisation, please contact us directly.

Type	D210/1204/IP/PTZ/P/0M
WISKA-Order no.	10113114
Material	Stainless steel
Surface	Powder coated
Colour	RAL 9016
Material Dome	polycarbonate
Operational areas	Outdoor
Weight	2,2 kg
Protection class	IP66, IP68 (0,2bar, 30min)
Temp. range min	-30 °C
Temp. range max	60 °C
Humidity	100 %
Wash&Wipe	No
Resolution	HDTV 1080p (2MP)
Image Sensor	1/2.8" Starvis CMOS
Video Standard	Digital
Video Streaming	H.264/MJPEG
Zoom	Yes
Zoom (opt. x digi.)	opt:4x / dig: yes
Frames per Second	30
Lighting Conditions	Low light
Min. illumination	0.005 lx (B/W)
Angle of View (horizontal)	101° - 51°
Angle of View (vertical)	53° - 29°
Pan/Tilt	Remote operated

Your Contact:

WISKA Hoppmann GmbH

Kisdorfer Weg 28 · 24568 Kaltenkirchen · Germany

☎ +49-4191-508-0 · 📠 +49-4191-508-209

contact@wiska.de · www.wiska.com

P/T-Type	included
Presets P/T	Yes
Rotation horizontal	355 °
Rotation vertical	+5° / +90°
Mounting	vertical, Upside down
Type of Voltage	POE+ (IEEE 802.at)
Wattage	13 W
Junction box required	No
CCTV add-on	BLC, HLC, WDR
Tariff number	85255000

Remarks:

IP Dome Camera, Outdoor, IP66/68,
 vandal resistant stainless steel housing
 with polycarbonate dome
 Resolution: 2MP/1080p/@ 50/30fps
 Zoom: 4x (optical), PTZ, Preset,
 Starlight technology
 Power: POE

12.05.2026

Your Contact:

WISKA Hoppmann GmbH
 Kisdorfer Weg 28 · 24568 Kaltenkirchen · Germany
 ☎ +49-4191-508-0 · 📠 +49-4191-508-209
 contact@wiska.de · www.wiska.com