

OSSP-R 75 / M75

Ex d stop end round, brass nickel-plated, M75



Products may differ in size, colour and appearance to those shown. If you require further information or customisation, please contact us directly.



Material	Brass nickel-plated
Material sealing gasket	CR
Temp. range min	-60 °C
Temp. range max	120 °C
Protection class	IP66 / IP67
Type of protection	Ex eb, Ex db, Ex tb
Ex-Certificate	ATEX, IECEx
Thread type	M
Ø Connection thread D	75
Lead	1,5
Length screw-in thread L	15 mm
Key width SW	10 mm
External diameter ED	88 mm
Total length TL	21 mm
Surface	Nickel-plated
Order no. nickel-plated	50065617
Type	OSSP-R 75 / M75
Packing unit	1
Tariff number	74198090
EAN number	4007685656177
ETIM-Classification	EC000032

23.05.2026


Your Contact:

WISKA Hoppmann GmbH

Kisdorfer Weg 28 · 24568 Kaltenkirchen · Germany

☎ +49-4191-508-0 · 📠 +49-4191-508-209

contact@wiska.de · www.wiska.com



Your Contact:

WISKA Hoppmann GmbH

Kisdorfer Weg 28 · 24568 Kaltenkirchen · Germany

☎ +49-4191-508-0 · 📠 +49-4191-508-209

contact@wiska.de · www.wiska.com