

6148/1111-111 portable lamp set

Ex LED Portable lamp with charging unit, polyamide, 3W IP66



Products may differ in size, colour and appearance to those shown. If you require further information or customisation, please contact us directly.



WISKA-Order no.	50102761
Type	6148/1111-111 portable lamp set
Material	Polyamide
Globe colour	Clear
Wattage	3 W
Voltage	230 V
Voltage min. (V)	12 V
Voltage max. (V)	240 V
Type of Voltage	AC / DC
Frequence	50/60 Hz
Protection class	IP66
Operational areas	Explosion protection, Outdoor
Temp. range min	-20 °C
Temp. range max	50 °C
Lightsource	LED
Lightsource incl.	Yes
Colour temperature	6500 K
Average lamp durability	35000 h
Approval	IBExU 11 ATEX 1066
Marking	II 2G Ex ib IIC T4 Gb, II 2D Ex tb IIIC T75°C Db
Explosion Groups	IIC
Temp.-class	T4
Zone	1
Colour	Black
Weight	1,83 kg

Your Contact:

WISKA Hoppmann GmbH

Kisdorfer Weg 28 · 24568 Kaltenkirchen · Germany

☎ +49-4191-508-0 · 📠 +49-4191-508-209

contact@wiska.de · www.wiska.com

Equipment:

- lead-fleece battery, maintenance-free, 6 V, 4.5 Ah
- Voltage charging unit: 12-30V DC and 110-240V AC, 50/60Hz
- lamps: main light, LED: 3 W; secondary light, LED: 0.5 W

Remarks:

Portable lamp 6148 with charging unit

Zones 1,2,21,22

Polyamide, impact resistant, black

Explosion protection: II 2G EEx ib IIC T4 Gb

Certificates: IBExU 11ATEX 1066, IECEx IBE 11.0009

Protection class to EN 60529:IP 66

with lead-fleece battery, maintenance-free,

6 V, 4.5 Ah

Voltage charging unit: 12-30V DC and

110-240V AC, 50/60Hz

lamps: main light, LED: 3 W

secondary light, LED: 0.5 W

12.05.2026

Your Contact:

WISKA Hoppmann GmbH

Kisdorfer Weg 28 · 24568 Kaltenkirchen · Germany

☎ +49-4191-508-0 · 📠 +49-4191-508-209

contact@wiska.de · www.wiska.com