

## WER-S-230AC-CL, signal light

LED Signal light clear 115 - 230V IP66/67



Products may differ in size, colour and appearance to those shown. If you require further information or customisation, please contact us directly.

<b>WISKA-Order no.</b>	50102888
<b>Type</b>	WER-S-230AC-CL, signal light
<b>Material</b>	Polypropylene
<b>Material globe/diffuser</b>	Polycarbonate
<b>Globe colour</b>	Clear
<b>Voltage min. (V)</b>	115 V
<b>Voltage max. (V)</b>	230 V
<b>Type of Voltage</b>	AC
<b>Protection class</b>	IP66 / IP67
<b>Temp. range min</b>	-25 °C
<b>Temp. range max</b>	50 °C
<b>Lightsource</b>	LED
<b>Lightsource incl.</b>	Yes
<b>Average lamp durability</b>	50000 h
<b>Ø cable diameter min</b>	6 mm
<b>Ø cable diameter max</b>	13 mm
<b>Mounting</b>	Wall, Ceiling, Surface mounting
<b>Colour</b>	Black
<b>External dimensions LxWxH</b>	85x85x72mm
<b>Weight</b>	0,13 kg
<b>Tariff number</b>	94051990

Remarks:

LED Permanent Light 115-230V AC

Housing WISKA-COMBI with 8 elastic self-sealing puncture-membranes for cable entry, 8 intergrated M20 thread for mounting without lock nut

Your Contact:

**WISKA Hoppmann GmbH**

Kisdorfer Weg 28 · 24568 Kaltenkirchen · Germany

☎ +49-4191-508-0 · 📠 +49-4191-508-209

contact@wiska.de · www.wiska.com

**Cable glands M20x1.5 to be ordered separately**

12.05.2026

Your Contact:

**WISKA Hoppmann GmbH**

Kisdorfer Weg 28 · 24568 Kaltenkirchen · Germany

☎ +49-4191-508-0 · 📠 +49-4191-508-209

contact@wiska.de · www.wiska.com