

WER-B-230AC-RD, Flash light

LED Flash light red 115 - 230V IP66/67



Products may differ in size, colour and appearance to those shown. If you require further information or customisation, please contact us directly.

WISKA-Order no.	50103018
Type	WER-B-230AC-RD, Flash light
Material	Polypropylene
Material globe/diffuser	Polycarbonate
Globe colour	Red
Voltage min. (V)	115 V
Voltage max. (V)	230 V
Type of Voltage	AC
Protection class	IP67
Temp. range min	-25 °C
Temp. range max	50 °C
Lightsource	LED
Lightsource incl.	Yes
Average lamp durability	50000 h
Type of cable gland	M 20 x 1,5
Ø cable diameter min	6 mm
Ø cable diameter max	13 mm
Mounting	Wall, Ceiling, Surface mounting
Colour	Black
External dimensions LxWxH	85x85x72mm
Weight	0,13 kg
Tariff number	94051990

Remarks:

LED Double flash light 115-230V AC

Your Contact:

WISKA Hoppmann GmbH

Kisdorfer Weg 28 · 24568 Kaltenkirchen · Germany

☎ +49-4191-508-0 · 📠 +49-4191-508-209

contact@wiska.de · www.wiska.com



Housing WISKA-COMBI with 8 elastic self-sealing puncture-membranes for cable entry, 8 intergrated M20 thread for mounting without lock nut
Cable glands M20x1.5 to be ordered separately

12.05.2026

Your Contact:

WISKA Hoppmann GmbH

Kisdorfer Weg 28 · 24568 Kaltenkirchen · Germany

 +49-4191-508-0 ·  +49-4191-508-209

contact@wiska.de · www.wiska.com